# **CERTIFICATE OF CONFORMITY**

## Certificate No.: LC21543-7

Project No.: 21543

Client No.: LC1234796

Applicant: Polishinterior S.C. ul. Majora 12A, 31-422 Krakow, Poland Date Issued: November 26, 2024

Certification System: Type 3 (ISO / IEC 17067)



Aun

Issued by:

**Certification Manager** 

# Products:

- AD104 Inswing Side-Hinged Door
- Model code PI-AD104-IGXX
- Performance Class/ Performance Grade Rating Class CW PG45
- Thermal simulation performed for five double- and triple-glazing options.

#### Legend for Coding System and Energy Performance Values:

• 'XX' is the applicable glazing option (5 options currently as shown below)

#### Glazing Options:

- Option 01: 6mm ExtraClear / 18mm 90% Argon / 6mm ClimaGuard Premium2
- Option 02: 4mm ClimaGuard Premium2 / 18mm 90% Argon / 4 mm ExtraClear / 18mm 90% Argon / 4mm ClimaGuard Premium2
- Option 03: 6mm ClimaGuard Premium2 / 16mm 90% Argon / 6mm ExtraClear / 16mm 90% Argon / 6mm ClimaGuard Premium2
- Option 04: 4mm SN70S / 18mm 90% Argon / 4 mm ExtraClear / 18mm 90% Argon / 4mm SN70S
- Option 05: 6mm SN70S / 16mm 90% Argon / 6 mm ExtraClear / 16mm 90% Argon / 6mm SN70S

#### Thermal Simulation Results:

- PI-AD104-IG01: U-Factor (BTU/h-ft2-°F): 0.326; SHGC: 0.358; VT: 0.458; L75: 0.5; ER: 19.
- PI-AD104-IG02: U-Factor (BTU/h-ft2-°F): 0.243; SHGC: 0.296; VT: 0.416; L75: 0.5; ER: 26.
- PI-AD104-IG03: U-Factor (BTU/h-ft2-°F): 0.241; SHGC: 0.289; VT: 0.409; L75: 0.5; ER: 26.
- PI-AD104-IG04: U-Factor (BTU/h-ft2-°F): 0.241; SHGC: 0.183; VT: 0.317; L75: 0.5; ER: 20.
- PI-AD104-IG05: U-Factor (BTU/h-ft2-°F): 0.239; SHGC: 0.181; VT: 0.311; L75: 0.5; ER: 20.

Page 1 of 2

The 'C' and 'US' indicators adjacent to the LabTest Certification Mark shall signify that the product has been evaluated by an accredited laboratory to the applicable Canadian and US Standards. The subject area shall be displayed with the LabTest Certification Mark to identify the Standard Number, and Revision Level.

ISO 17020

#### Applicable requirements:

- > AAMA/WDMA/CSA 101/I.S.2/A440-17
- > CSA A440S1:19
- > CSA A440.2:22

## Conditions of acceptability:

> Products are certified for Canadian Market only

# General Note:

Refer to LC Listing Report no. 40.00.21543-7\_Rev.0

Page 2 of 2

The 'C' and 'US' indicators adjacent to the LabTest Certification Mark shall signify that the product has been evaluated by an accredited laboratory to the applicable Canadian and US Standards. The subject area shall be displayed with the LabTest Certification Mark to identify the Standard Number, and Revision Level.